

M22常溫型技術參數 Technical data for normal temperature type

DC-220V, TD-50%

型號Model		M22-8060L	M22-11060L	M22-120100L	M22-140100L	M22-140150L
外形尺寸overall dimension(mm)	A	800	1100	1200	1400	1400
	B	600	600	1000	1000	1500
	C	900	900	950	1100	1100
	D	300	300	300	900	900
	E	110	110	125	125	125
	F	180	180	200	200	200
	G	32	32	38	38	38
品質Mass (kg)		1000	1300	2400	2000	3000
電流 current (A)		34.1	27.3	45.5	63.6	81.9
功率power (kw)		7.5	6	10	14	18
起吊能力(表內大截面工字鋼如果沒有捆紮也可吊起一層) lifting capacity(if the big cross section double T-steel in the table is not bundled, one level can be lifted)	最小規格 Min.Specifications	10號工字鋼 No.10 double T-steel	10號工字鋼 No.10double T-steel	10號工字鋼 No.10 double T-steel	10號工字鋼 No.10 double T-steel	10號工字鋼 No.10 double T-steel
	最大規格 Max.Specifications	20a號工字鋼 No.20a double T-steel	30a號工字鋼 No.30a double T-steel	63a號工字鋼 No.63a double T-steel	50a號工字鋼 No.50a double T-steel	50a號工字鋼 No.50a double T-steel
	最大長度 (mm) Max.Length	2000	2000	2000	2000	2000
	捆紮寬度 (mm) width of bundle	500	500	1000	650	650
	單捆重量 (kg) weight of single bundle	5000	4000/6000	15000	3000/5000	4500/6000
	捆數number of bundle	四臺吊1捆4units lift 1 bundle	四臺吊2/1捆4units lift 2/1 bundle	四臺吊1捆4units lift 1 bundle	四臺吊4/2捆4units lift 4/2 bundles	四臺吊4/2捆4units lift 4/2 bundles